

START 356 (type A)
STARTER FOR 3-PHASE PUMPS MAX 600 V
without thermal contacts built-in
SPECIALLY DESIGNED FOR
THE NORTH AMERICAN MARKET
CSA-APPROVED

Portable Hand-operated 3-phase starter for
D-O-L start of pumps **without thermal contacts.**

Type: START 356-600-A-PG-XX
Voltage: max 600 V
Frequency: 50-60 Hz
Monitoring: Thermal/magnetic overload protection
Connection supply: Terminal connection with cable glands for cable 13-25 mm
Connection pump: Terminal connection with cable glands for cable 9-18 mm
Current range: 1,0 - 25 Amps
General: Degree of protection IP55
Size 255 x 168 x 100 mm
Weight 2,7 kg
Approved by CSA



Type	Voltage	Current range	Supply cable Ø	Pump cable Ø	Part no	Price
START 356-600-A-PG- 1,6	≤ 600 V	1,0 - 1,6	13 - 20 mm	13 - 18 mm	554 20 00	
-"- 2,5	-"-	1,6 - 2,5	-"-	-"-	554 20 01	
-"- 4	-"-	2,5 - 4,0	-"-	-"-	554 20 02	
-"- 6	-"-	4 - 6	-"-	-"-	554 20 03	
-"- 10	-"-	6 - 10	-"-	-"-	554 20 04	
-"- 16	-"-	10 - 16	-"-	13 - 20 mm	554 20 05	
-"- 20	-"-	14 - 20	-"-	18 - 25 mm	554 20 06	
-"- 25	-"-	18 - 25	-"-	-"-	554 20 07	